

Table 3
Recommended Maximum Interior or Exterior Swinging Door Sizes

Fully Tempered Glass							
		Full Rails			Patch Fittings		
Glass Thickness Glass Weight		10mm (3/8") [5 lbs/sf]	12mm (1/2") [6.5 lbs/sf]	19mm (3/4") [10 lbs/sf]	10mm (3/8") [5 lbs/sf]	12mm (1/2") [6.5 lbs/sf]	19mm (3/4") [10 lbs/sf]
Concealed Overhead	Width	914mm (36 in.)	1065mm (42 in.)	914mm (36 in.)	914mm (36 in.)	1065mm (42 in.)	914mm (36 in.)
	Height	2130mm (84 in.)	2740mm (108 in.)	2130mm (84 in.)	2130mm (84 in.)	2590mm (102 in.)	2130mm (84 in.)
Closer	Glass Weight	(105 lbs.)	(205 lbs.)	(210 lbs.)	(105 lbs.)	(194 lbs.)	(210 lbs.)
Floor Closer	Width	914mm (36 in.)	1220mm (48 in.)	1220mm (48 in.)	914mm (36 in.)	1065mm (42 in.)	914mm (36 in.)
	Height	2130mm (84 in.)	2740mm (108 in.)	3048mm (120 in.)	2130mm (84 in.)	2590mm (102 in.)	2440mm (96 in.)
	Glass Weight	(105 lbs.)	(234 lbs.)	(400 lbs.)	(105 lbs.)	(194 lbs.)	(240 lbs.)